




OUTLINE DIMENSIONS
3-PHASE INDUCTION MOTOR

FRAME NO :
D315SC

POLES	HP	KW	SYNCH RPM
4	175	132	1500
6	125	90	1000
8	100	75	750

TOTALLY ENCLOSED FAN-COOLED TYPE, SQUIRREL-CAGE ROTOR



DIMENSIONS IN MM

FRAME NO.		A	AA	AB	AC	AD	AE	AF	B	BA	BB	C
315SC		508	115	615	642	620	465	312	406	115	490	216
D	E	ED	EE	F	G	GA	H	HA	HD	K	L	LE
85	170	140	157	22	76	90	315	40	723	28	1161	369

NOTES:

1. FOOT MOUNTED IM1001.
2. TYPICAL DIMENSIONS ONLY
FOR CERTIFIED DIMENSIONS
REFER TO TECO.
3. FOR BELT OR DIRECT DRIVE.

FOR MAXe3MINING AND
MAXe3PREMIUM SEVERE DUTY

DWN.	EJ	01. 12. 15	東元電機股份有限公司 TECO ELEC. & MACH. CO., LTD. TAIWAN R. O. C.	REV : 00
CHKD.	DK	01. 12. 15		
APPD.	JF	01. 12. 15		